



Green Ballast Daylight Harvesting Ballast

Programmed Start Dimming Electronic Fluorescent Ballast
Self-Contained Automatic Lighting Control

APPLICATION and PERFORMANCE SPECIFICATION

GB2T832DHB-U

2-Lamp 32 Watt T8

Catalog Number	Dip Switch Tuning	Input Watts	Input Amps	Ballast Factor
GB2T832DHB-U	100% - Min	62/10	0.53	0.99
	90%	58	0.49	0.87
	80%	55	0.46	0.80
	70%	49	0.41	0.68
	60%	47	0.40	0.64
	50%	41	0.35	0.53
	40%	37	0.32	0.45
Max Dimming		18	0.15	

Total Harmonic Distortion <10% at full output. Power Factor > 98% Lamp Crest Factor <1.7%

Performance:

- Meets NEMA Standard LL9-2009
- Meets ANSI Standard C62.41
- Meets FCC Title 47 CFR, Class A Part 18
- ISO 9002 Manufactured

Safety

- No PCB's
- UL C-US Listed

Application Parameters

- Minimum Starting Temperature 32° F
- 5 Year Limited Warranty
- Sound Rating Class A

Physical

Length	17.0"
Width	2.25"
Height	1.0"
Weight	1.10 lbs



Application and Performance Information Subject to Change without Notification

