



FLUORESCENT BALLAST SPECIFICATIONS

GB3T832DHB-U



DESCRIPTION

CATALOG NO.	TYPE	STARTING METHOD	LAMPS	LAMP TYPE
GB3T832DHB-U	Electronic	Program Rapid Start	3	F32T8, F32T8/U, F31T8/U

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE	FREQUENCY	LAMP WATTS	INPUT WATTS	INPUT CURRENT	THD	PF	Sound Rated A
120V~277V	50/60Hz	32W, 32W, 31W	86.5W/85.5W	0.71A/0.31A	<10%	.99	No PCBs
MIN START TEMP	BALLAST FACTOR	BEF	O.C.V	BALLAST FREQ	Class P		
32°F~0°C	0.88	1.02/1.03	300VRMS	>40kHz	Type 1 Outdoor		

CASE DIMENSIONS

UNITS	M	Length	Width	Height
INCHES	16.20	16.88	2.25	1.00
TOL(+/-)	0.05	0.05	0.05	0.05

CONNECTOR WIRETRIP

COLOR	BLACK	WHITE	GREEN	RED	YELLOW	BLUE	BROWN
NUMBER	1	1	1	2	3	4	1

Cat. No. GB3T832DHB-U
Type 1 Outdoor
Program Rapid Start
Start Temp: 32°F~120°F
Lamp Type: 3°F32T8, 3°F32T8/U, 3°F31T8/U
www.greenballastinc.com | 1-800-409-1453

Sound Rating A
O.C.V.: 300VRMS
Class P
NO PCB's

Input: 120 to 277 V 50/60Hz
Max. Line Current 120V: 0.71A, 277V: 0.31A
Power Factor > 0.99 Max. Line Current THD < 10%

Daylight Harvesting
ELECTRONIC BALLAST
LISTED E236937 8LA5
DATE:

WARNING Risk of Electric Shock

- Turn power off before servicing
- properly ground ballast and fixture

Use 18 AWG Solid Copper Wire Rated ≥ 600V Stripped to 0.33"

